



Manufacturers of Carpet Cleaning Equipment,
Chemicals, and Janitorial Supplies.
1428 Blalock, Houston, TX 77055
(713) 932-8293 * Fax (713) 932-7605

MATERIAL SAFETY DATA SHEET

AND SAFE HANDLING AND DISPOSAL INFORMATION

DATE: MAY 29, 1990

PRODUCT NAME: FIBER GUARD

SUPERSEDES: ALL PREVIOUS

PRODUCT NUMBER: 2049

PG 1/2

SECTION I - EMERGENCY CONTACTS

NAMCO MANUFACTURING INC. (713) 932-8293 OR (800) 634-5816

POISON CENTER: (800) 764-7661

SECTION II - HAZARDOUS INGREDIENTS

NONE

SECTION III - PHYSICAL DATA

CHEMICAL NAME - CENEKOL FT SUPRA, DYE FIXATIVE

SOLUBILITY IN WATER - COMPLETE

APPEARANCE & ODOR - LIGHT TAN, SLIGHT PHENOLIC ODOR

SECTION IV - FIRE & EXPLOSION HAZARD DATA -

FLASH POINT (METHOD USED): 200° F (PMCC)

EXTINGUISHING MEDIA: WATER, DRY CHEMICAL, CO₂

UNUSUAL FIRE & EXPLOSION HAZARDS: NONE EXPECTED

SPECIAL FIRE FIGHTING PROCEDURES: WEAR S C B A

SECTION V - REACTIVITY DATA -

STABILITY: STABLE

HAZARDOUS DECOMPOSITION PRODUCTS: BURNING WILL PRODUCE OXIDES OF CARBON & NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - SPILL OR LEAK PROCEDURES -

SPILL OR RELEASE CONTROLS - WASH DOWN WITH WATER IF RELEASED OR SPILLED

WASTE DISPOSAL METHOD - BURY OR INCINERATE ACCORDING TO FEDERAL, STATE, & LOCAL REGULATIONS.

SECTION VII - HEALTH HAZARDS

ACUTE EFFECTS:

EYES: IRRITATION

FIRST AID PROCEDURES:

SKIN: WASH THOROUGHLY WITH SOAP AND WATER

INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULTY, GIVE WATER AND SEEK MED. CARE

EYES: FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL AID.

INGESTION: DILUTE WITH WATER AND INDUCE VOMITING. GET IMMEDIATE ATTENTION.

HEALTH : 0
FIRE : 1
REACTIVITY : 0
SPECIAL : 0

SECTION VIII - SPECIAL PROTECTION INFORMATION

VENTILATION: LOCAL

PROTECTIVE GLOVES: RUBBER

EYE PROTECTION: GOGGLES

OTHER PROTECTIVE EQUIPMENT: COVERALL OR APRON TO MINIMIZE SKIN CONTACT.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: IN ACCORD WITH GOOD INDUSTRIAL PRACTICE, HANDLE WITH CARE AND AVOID PERSONAL CONTACT.

SECTION X - DILUTION RATIO

FULL 7.4264 %
