



Manufacturers of Carpet Cleaning Equipment,
Chemicals, and Janitorial Supplies.
1651 Blalock, Houston, TX 77055
(713) 932-8293 * Fax (713) 932-7605

MATERIAL SAFETY DATA SHEET
AND SAFE HANDLING AND DISPOSAL INFORMATION

DATE: DECEMBER 18, 2005

PRODUCT NAME: LEMON OIL FURNITURE POLISH

SUPERSEDES: ALL PREVIOUS

PRODUCT NUMBER: 2021

PG 1/2

SECTION I - EMERGENCY CONTACTS

NAMCO MANUFACTURING INC. (713) 932-8293 OR (800) 634-5816

POISON CENTER: (800) 764-7661

SECTION II - HAZARDOUS INGREDIENTS

SOLVENTS: 100%

SECTION III - PHYSICAL DATA

CHEMICAL NAME AND SYNONYMS: HYDROCARBON DISTILLATE - SEAL OIL

BOILING POINT - 475-610 °F

VAPOR PRESSURE (mmHg): LESS THAN 100 MICRONS OF MERCURY AT 100° F

PERCENT VOLATILE BY VOLUME (%): 100%

VAPOR DENSITY (AIR=1): 8.0

SOLUBILITY IN WATER - INSOLUBLE

SPECIFIC GRAVITY (H 20 = 1) - .8155

APPEARANCE & ODOR - CLEAR LIQUID, LEMON ODOR

SECTION IV - FIRE & EXPLOSION HAZARD DATA -

FLASH POINT (method used): ASTM D93, 265° F

EXTINGUISHING MEDIA: FOAM, DRY CHEMICAL OR CO₂, DO NOT USE DIRECT WATER STREAM

SPECIAL FIRE FIGHTING PROCEDURES: WHATEVER LOCAL FIRE PROTECTION DEPARTMENT CONSIDERS SUITABLE FOR COMBATING HYDROCARBON FIRES.

SECTION V - REACTIVITY DATA -

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - SPILL OR LEAK PROCEDURES -

SPILL OR RELEASE CONTROLS - REMOVE IGNITION SOURCES. DO NOT FLUSH TO SEWER OR OPEN WATER. PICK UP INERT ABSORBENT - PLACE IN CLOSED CONTAINER FOR DISPOSAL.

WASTE DISPOSAL METHOD - UTILIZE LICENSED WASTE DISPOSAL

SECTION VII - HEALTH HAZARDS

ACUTE EFFECTS:

IRRITANT TO EYES AND SKIN, MAY CAUSE DERMATITIS. POSSIBLE EFFECTS INCLUDE HEADACHES, DROWSINESS, NAUSEA, FATIGUE, PNEUMONITIS, PULMONARY EDEMA, CENTRAL NERVOUS SYSTEM, DEPRESSION & RESPIRATORY IRRITANT.

FIRST AID PROCEDURES:

SKIN: WASH THOROUGHLY WITH SOAP AND WATER FOR 15 MINUTES.

INGESTION: DO NOT INDUCE VOMITING, CALL A PHYSICIAN

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION ASAP.

HEALTH : 0
FIRE : 2
REACTIVITY : 0
SPECIAL : 0

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: UP TO 25mg/m³ 1/2 MASK ORGANIC VAPOR RESPIRATOR

VENTILATION: LOCAL OR DILUTION VENTILATION

PROTECTIVE GLOVES: RUBBER

EYE PROTECTION: CHEMICAL OR SAFETY GOGGLES.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: STORE AWAY FROM HEAT OR OPEN FLAME

DO NOT STORE WITH STRONG OXIDIZERS.
